


ELECTRICAL SPECIFICATIONS

Frequency Range: 1.28-1.32 GHz
 Impedance: 50 Ohm
 Insertion Loss: 0.30 dB max.
 Isolation: 23 dB min.
 VSWR: 1.20 max.
 Forward Power: 60W
 Direction: Clockwise

Revisions			
Rev	Description	Date	Approved:
A	Initial Release	2015.6.19	A. M



NOTES:
 1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
 2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

Drawn:	W. Y 2015.6.19
Checked:	T. L 2015.6.19
Approved:	A. M 2015.6.19
Unless Otherwise Specified Dimensions are in Millimeters, Dimensions in [] are in Inches for Customer Reference Only. Unless Otherwise Specified Tolerance are: .XX ±0.13 [.005"] .X ±0.20 [.008"] X ±0.50 [.019"] .X° ±1° X° ±2°	

Title:	SMA Circulator Freq 1.28-1.32 GHz
Part No:	DCC128132

DEEWAVE
www.deewave.com

View:

Size:	Scale:	Sheet:	Rev:
A3	2:1	1/1	A