


ELECTRICAL SPECIFICATIONS

Frequency Range: 869-894 MHz
 Impedance: 50 Ohm
 Insertion Loss: 0.60 dB max.
 Isolation: 50 dB min.
 VSWR: 1.20 max.
 Forward Power: 150 W
 Direction: Clockwise

Revisions			
Rev	Description	Date	Approved:
A	Initial Release	2017.2.23	A. M



- NOTES:
1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
 2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

Drawn:	W. Y 2017.2.23
Checked:	T. L 2017.2.23
Approved:	A. M 2017.2.23
Unless Otherwise Specified Dimensions are in Millimeters, Dimensions in [] are in Inches for Customer Reference Only. Unless Otherwise Specified Tolerance are: .XX ±0.13 [.005"] .X ±0.20 [.008"] X ±0.50 [.019"] .X° ±1° X° ±2°	

Title:	SMA Female Dual Junction Circulator, Freq 869-894 MHz
Part No:	DDCC086089

DEEWAVE
www.deewave.com

View:

Size:	Scale:	Sheet:	Rev:
A3	2:1	1/1	A